#### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		BLM - EXIS	STING VI	SUAL SE	TTING				BLM - VI	SUAL CO	NTRAST A	NALYSIS			PACT ICANCE
Key Viewpoint	Description	Scenic Quality C	classification	Viewer Sensitivity			VRM Class			Level of Chan	<b>J</b>	VRI	M Consister	псу	Before Mitigation	Mitigation
(KVP)				,	Status	Rating	Mana	gement Obj	ective	Contrast Rating Work	sheets)				After Mitigation	
KVP 1 Big Horn Mountains Proposed Project Figures D.3- 2A / 2B	View to the north-northwest toward existing DPV1 Towers A358 through A362, from a 4WD access road south of the Big Horn Mountains and north of I-10.	Not Avail  (Wherever "Not Availabl specific data field of the classification was origin the BLM and the specific Quality or Viewer Sensit documented or is otherw	le" is indicated in a nis table, the VRM nally determined by ic data field [Scenic tivity] either was not	ot Available	Existing RMP (Resource Management Plan)	III	moderate. Mattract attention the view of the should repeat the predomir	The level of stic landscape lanagement A on but should casual observers.	change to the should be ctivities may not dominate ver. Changes nents found in atures of the	Low The DPV2 line would be be and slightly to the south of DPV1 transmission line, structures and conductor visible, though not promitive wing distance. The new would be the same design as the existing structures, a weak level of visual of the province o	of the exiting The new The new The would be The nent at this The structures The and height The resulting in	elements of the in the lands characteristic though the pwould not compare the second control of the second con	objective of a of visual chan	moderate (or age. While the t the basic tural features repeat the ag line. And be visible, it view of the	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
VIEW	POINT		CPUC - EX	ISTING V	ISUAL S	ETTING				CF	PUC - VIS	UAL CHAN	GE			PACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibilit	Distan Zone	OT.	er Duration	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 2 Interstate 10 Crossing Harquahala Plain Proposed Project Figures D.3- 3A / 3B	View to the west toward existing DPV1 Towers A310 through A314, from westbound I-10, 1.5 miles west of Avenue 75E.	Low-to-Moderate Foreground to background relatively non-descript, flat, grass- and shrub covered plain, punctuated by prominent utility towers with industrial character. Backdropped by undulating mountain ranges low on the horizon. Interstate 10 is a prominent linear feature bisecting the plain.	Moderate Travelers on I-10 are provide panoramic views across a brown flat plain to distant mountain ranges. Although some traveled may anticipate the occasional energy infrastructure, any addition of industrial character the predominantly natural appearing landscape or blockatof views to more valued landscape features (distant mountains) would be seen as a adverse visual change.	ers al High	Foregro	und High	Extended	High	Moderate	Structures D-33 through D-37 of the DPV2 line would be built adjacent and slightly to the southeast of the existing DPV1 line. The new and existing towers would appear similar in design and height and would be paired up. The new structures would cause a noticeable increase in structure prominence and industrial character within the corridor. Additional skylining (extending above the horizon line) and view blockage of background sky and distant mountains would also occur.	Moderate	Co- Dominant	Low to Moderate	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

#### METHODOLOGIES:

VRM

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		CPUC - EXIST	TING VIS	SUAL SETT	ING				СР	UC - VIS	UAL CHAN	GE			ACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Viev Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ——— After Mitigation	Mitigation
KVP 33 Pacific Crest Trail and Snow Creek Road  Devers-Valley Alternative  Figures D.3-34A / 34B	View to the west toward existing Devers-Valley towers, from Pacific Crest Trail, just west of Snow Creek Road.	Moderate Foreground flat desert landscape backdropped by the rugged and steeply-rising northern ridges of the San Jacinto Mountains. The existing Devers-Valley transmission line is a prominent feature made more noticeable by the visible skylining (extending above the horizon line) that occurs when viewped from lower elevation viewpoints such as the Snow Creek Village residential community and the Pacific Crest Trail.	High Residents of the Snow Creek Village residential community and hikers on the Pacific Crest Trail would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky and mountain ridges) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	D-V2 structures would be built adjacent and slightly to the east (or south) of the existing D-V1 line. The new and existing towers would appear similar in design and height and would be paired up. The new structures would cause a noticeable increase in structure prominence and industrial character within the corridor. Additional skylining and view blockage of background sky and mountain ridges would also occur.	Moderate	Co- Dominant	Moderate	Moderate	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-40 (Project Design)
KVP 34 Riza Avenue in Cabazon Devers-Valley Alternative Figures D.3-36A / 36B	View to the northeast toward existing Devers-Valley towers DV 49 through DV 51, from Riza Avenue, approximately 0.2 mile west of Elm Street in Cabazon.	Low to Moderate Foreground relatively non- descript, grass- and shrub- covered desert landscape punctuated by rural residences and prominent utility towers with industrial character. Backdropped by undulating mountain ridges and a wind farm development to the east.	High Although existing energy transmission infrastructure features prominently in the landscape visible from within this community, residential viewers would consider any increase in industrial character, structure, prominence, or view blockage of higher value landscape features (background sky and mountain ridges) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	D-V2 structures would be built adjacent and slightly to the south of the existing D-V1 line. The new and existing towers would appear similar in design and height and would be paired up. The new structures would cause a substantial increase in structure prominence and industrial character within the corridor. Additional skylining and view blockage of background sky and mountain ridges would also occur.	Moderate to High	Co- Dominant	Moderate to High	Moderate to High	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-40 (Project Design)

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	/POINT		CPUC - EXIS	TING VIS	SUAL SETT	ING				СР	UC - VIS	UAL CHAN	GE			PACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Viev Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 35 State Route 243 Devers-Valley Alternative Figures D.3-37A / 37B	View to the east toward existing Devers-Valley towers DV 73 through DV 75, from southbound SR 243, just north of the SR 243 span.	Moderate Panoramic view of San Gorgonio Pass and the northern ridges of the San Jacinto Mountains. Foreground views dominated by rugged, rocky ridgelines, punctuated by prominent utility towers with industrial character. Backdropped by urban development within San Gorgonio Pass and more distant mountains.	High  SR 243 is a State designated Scenic Highway and therefore warrants a high rating for viewer concern. Although some travelers may anticipate the presence of existing energy infrastructure, any addition of industrial character or prominence or blockage of higher quality landscape features (sky, mountain ridges, or panoramic views of the Pass) would be seen as an adverse visual change.	High	Foreground	Moderate	Moderate to Extended	Moderate to High	Moderate to High	D-V2 structures would be built adjacent and slightly to the south of the existing D-V1 line. The paired new and existing towers would appear similar in design and height but would be offset in elevation due to the slope and variation in terrain. The new structures would cause a substantial increase in structure prominence and industrial character within the corridor as viewed from SR 243. Additional skylining and view blockage of background sky, mountain ridges, and the Pass would also occur.	Moderate to High	Co- Dominant	Moderate	Moderate	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-40 (Project Design)
KVP 36 Mapes Road west of Menifee Road Devers-Valley Alternative Figures D.3-40A / 40B	View to the south toward existing Devers- Valley towers DV 146 through DV 151, from Mapes Road, just west of Menifee Road.	Moderate Foreground, open views of a flat rural residential landscape consisting of grass-covered fields punctuated by numerous residences and prominent, structurally complex utility towers with industrial character. Backdropped by the undulating ridges of more distant hills and mountains.	High Although existing energy transmission infrastructure features prominently in the landscape, residential viewers would consider any increase in industrial character, structure, prominence, or view blockage of higher value landscape features (background sky and mountain ridges) an adverse visual change.	High	Foreground	Moderate	Extended	High	Moderate to High	D-V2 structures would be built adjacent and slightly to the east of the existing D-V2 line. The new and existing towers would appear similar in design and height and would be paired up. The new structures would cause a substantial increase in structure prominence and industrial character within the corridor. Additional skylining and view blockage of background sky and mountain ridges would also occur.	Moderate to High	Co- Dominant	Moderate to High	Moderate to High	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-40 (Project Design)

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		BLM - EXIS	STING VI	SUAL SE	TTING				BLM - VI	SUAL CO	NTRAST A	NALYSIS			PACT FICANCE
Key Viewpoint (KVP)	Description	Scenic Quality C	lassification	Viewer Sensitivity	Status	Rating	VRM Class	gement Obj	ective	Level of Chang (See Appendix VR Contrast Rating Works	-2	VRI	M Consisten	су	Before Mitigation ————————————————————————————————————	Mitigation
KVP 3 Eagletail Mountains Access Proposed Project Figures D.3- 4A / 4B	View to the northwest toward existing DPV1 Towers A422 through A303, from Eagletail Mountains BLM access road YE047 at the north end of the Eagletail Mountains.	Not Avail	lable No	ot Available	Existing RMP	III	moderate. Nattract attention the view of the should repeat the predomin	The level of a stic landscape lanagement A on but should a casual observers.	change to the should be ctivities may not dominate ver. Changes nents found in atures of the	Low to Moderate The DPV2 line would be be and slightly to the south of DPV1 transmission line. structures and conductors visible slightly to the east (existing towers, effectived the number of visible townew structures would be design and height as the structures The resulting contrast would be weak to	uilt adjacent i the exiting The new is would be right) of the y doubling vers. The the same e existing	The low to r would meet the a moderate ( change. Wh repeat the bas natural feature repeat the chaline. And the visible, it would the casual of	or lower) degr ile the new line sic elements o	Il objective of see of visual e would not if the existing cape, it would if the existing ct would be e the view of viewed from	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
VIEW	POINT		CPUC - EXI	STING V	ISUAL S	ETTING				СР	UC - VIS	UAL CHAN	GE			PACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibilit	Distan Zone	Ot.	er Duration	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 4 Crystal Hill Road Kofa NWR Proposed Project Figures D.3- 5A / 5B	View to the southeast toward existing DPV1 Towers A740 through A743, from Crystal Hill Road in KOFA National Wildlife Refuge, approximately 4.8 miles east of U.S. 95.	Moderate Foreground flat desert landscape backdropped by rugged, angular mountains with a very coarse texture. The existing DPV1 transmission line with its contrasting industrial character compromises the otherwise natural appearing landscape, reducing landscape coherence and overall visual quality to a moderate level.	High Travelers on Crystal Hill Road Kofa National Wildlife Refuge a typically pursuing back-countr and off-highway recreation opportunities in a predominant natural desert setting. Any addition of developed industria features to the landscape or blockage of views to higher quality landscape features (Livingston Hills) would be perceived as an adverse visua change in the landscape.	are y cly High	Foregro	und Low	Extended	Moderate to High	Moderate to High	Structures F-50 through F-53 of the DPV2 line would be built adjacent and slightly to the south of the existing DPV1 line. The new towers would appear similar in design and height and would be paired with the existing towers. The new structures would cause a noticeable increase in structure prominence and industrial character along the corridor. Additional view blockage of background sky and the Livingston Hills would also occur.	Moderate	Co- Dominant	Moderate to High	Moderate	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	/POINT	BLM - E	EXISTING V	ISUAL SE	TTING		BLM - VISUAL CO	NTRAST ANALYSIS		PACT
Key			Viewer			VRM Class	Level of Change	VDW 0	Before Mitigation	
Viewpoint (KVP)	Description	Scenic Quality Classification	Sensitivity	Status	Rating	Management Objective	(See Appendix VR-2 Contrast Rating Worksheets)	VRM Consistency	After Mitigation	Mitigation
KVP 5 U.S. 95 Crossing Kofa Entrance Proposed Project Figures D.3-6A / 6B	View to the north toward existing DPV1 Towers A720 and A721, from northbound U.S. 95, just south of the Crystal Hill Road entrance to Kofa National Wildlife Refuge.	Not Available	Not Available	Existing RMP	III	To partially retain the existing character of the landscape. The level of change to the characteristic landscape should be moderate. Management Activities may attract attention but should not dominate the view of the casual observer. Changes should repeat the basic elements found in the predominant natural features of the characteristic landscape.	Low The DPV2 span of US 95 would occur immediately south of the existing DPV1 transmission line. The proposed project would effectively double the number of visible structures and conductors from US 95. However, the new structures would be the same design and height as the existing structures and would not substantially change the character of the existing landscape. The resulting visual contrast would be weak.	Consistent The low level of change would meet the VRM Class III objective of a moderate (or lower) degree of visual change. While the new line would not repeat the basic elements of the existing natural features in the landscape, it would repeat the characteristics of the existing line. And though the project would be visible, it would not dominate the view of the casual observer when viewed from northbound or southbound US 95.	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	<b>Measure</b> V-3 (Project Design)
KVP 6 Copper Bottom Pass Proposed Project Figures D.3- 7A / 7B	View to the east- southeast toward existing DPV1 Tower 493, from Pipeline Road, just south of Copper Bottom Pass in the Dome Rock Mountains.	Not Available	Not Available	Existing RMP	III	To partially retain the existing character of the landscape. The level of change to the characteristic landscape should be moderate. Management Activities may attract attention but should not dominate the view of the casual observer. Changes should repeat the basic elements found in the predominant natural features of the characteristic landscape.	Moderate The Proposed Project would parallel the existing DPV1 line to the south. Although the new structures would be the same design and height as the existing structures, the new line would cause some additional view blockage of the adjacent ridges and slopes when viewed from the 4WD access road. The new line would also increase the structural complexity and industrial character in the narrow valley landscape with confined views. The resulting visual contrast for form and line would be moderate.	Consistent The moderate level of change would meet the VRM Class III objective of a moderate (or lower) degree of visual change. The new line would not repeat the basic elements of the existing natural features in the landscape and would increase the industrial character of the existing landscape somewhat. However, the new line would repeat the characteristics of the existing line and it would not dominate the view from the 4WD access road to Copper Bottom Pass.	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
KVP 7 Colorado River Crossing Proposed Project Figures D.3- 8A / 8B	View to the southwest (down river) toward existing DPV1 Towers B801 and B802, from the Colorado River, north of the crossing.	Not Available	Not Available	Existing RMP	II (Inside River/ Riparian Corridor)  III (Outside River/ Riparian Corridor)	Class II  To retain the existing character of the landscape. The level of change to the characteristic landscape should be low. Management activities may be seen, but should not attract the attention of the casual observer. Any changes must repeat the basic elements of form, line, color, and texture found in the predominant natural features of the characteristic landscape.  Class III  See Above	Low (for conductors) Moderate (for structures) The Proposed Project would parallel the existing DPV1 line to the north. Although the new structures would be the same design and height as the existing structures, the new structures would "skyline" (extend above the horizon line) as they approach the span of the river. As a result, some additional view blockage of sky would occur as boaters approach the span. The new line would also increase the structural complexity and industrial character visible from the river. The resulting visual contrast for form and line would be moderate.	Consistent The span (conductors) over the river (Class II) and the low level of change resulting from the additional conductors would meet the VRM Class II objective of a low degree of visual change.  The moderate level of change associated with the structures would meet the VRM Class III objective of a moderate (or lower) degree of visual change. While the new line would not repeat the basic elements of the existing natural features in the landscape, it would repeat the characteristics of the existing line and it would not dominate the view from the river.	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	/POINT		CPUC - E	EXISTING	VISUAL :	SETTING					СР	PUC - VIS	UAL CHAN	IGE		IMP.	ACT CANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibi	ity Dista	nce	mber of ewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 8 State Route 78 Crossing - Ripley Proposed Project Figures D.3- 9A / 9B	View to the north toward existing DPV1 Towers 4735XX and 4736XX, from northbound State Route 78, just north of the community of Ripley.	Low-to-Moderate Foreground to middleground, modified landscape consisting of level agricultural fields characterized by flat, valley floor landform with horizontal lines, punctuated by the vertical forms and industrial character of utility infrastructure. Backdropped by distant mountain ranges low on the horizon with irregular, undulating lines.	High Travelers on SR 78, include residents of Ripley anticipate rural, agricultural character of Palo Verde Valley landscape well as the substantial pressof the existing electric transmission and roadside infrastructure. However, a increase in industrial charactincrease in view blockage distant mountain ranges a panoramic sightlines would seen as an adverse visu change.  BLM - E	te the of the pe as sence utility any otter or e of and d be			derate	Moderate to Extended	Moderate to High	Moderate	Structures 2735 and 2736 of the DPV2 line would be built adjacent and slightly to the north of the existing DPV1 line. The new and existing towers would appear similar in design and height and would be paired up. The new structures would cause a noticeable increase in structure prominence and industrial character when viewed from SR 78. Additional view blockage of background sky and mountains would also occur.	Low to Moderate	Co- Dominant	Moderate NAL YSIS	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	
Key Viewpoint	Description	Scenic Quality C		Viewer			V	RM Class			Level of Chan	ge		M Consisten		SIGNIFI Before Mitigation	Mitigation
(KVP)		Coomo Caamy		Sensitivity	Status	Rating	ı	Manaç	gement Obje	ective	(See Appendix VF Contrast Rating Works				,	After Mitigation	,ga.io.i.
KVP 9 Chuckwalla Valley	View to the east- southeast toward existing DPV1 Towers 4546XX through	Class The landform of the centra Chuckwalla Valley floor is fla grass and low-growing shrubs	I-eastern portion of the at and non-descript with	High (Note: All BLM lands within the study area in California are				e landscape. characteris	ain the existing The level of o tic landscape s anagement Ao	change to the should be	Low The Proposed Project wo the existing DPV1 line to Although the new structure the same design and hei existing structures, the nei would cause additional (extend above the horize they cross the floor of C	the north. es would be ight as the w structures skylining on line) as	VRM Class III lower) degree		moderate (or ge. While the	BEFORE: Adverse but Less Than Significant (Class III)	Measure V-3

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

S-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT	BLM - E	XISTING VI	SUAL SE	TTING		BLM - VISUAL CO	NTRAST ANALYSIS		PACT ICANCE
Key Viewpoint	Description	Scenic Quality Classification	Viewer			VRM Class	Level of Change	VRM Consistency	Before Mitigation	Mitigation
(KVP)	Description	Scenic Quality Glassification	Sensitivity	Status	Rating	Management Objective	(See Appendix VR-2 Contrast Rating Worksheets)	VAIN Consistency	After Mitigation	Mitigation
KVP 10 Alligator Rock ACEC Proposed Project Figures D.3- 11A / 11B	View to the east- southeast toward existing DPV1 Towers 4515X through 4518XX, from an access road within the Alligator Rock ACEC, south of I-10 and Desert Center.	Class B  The landscape consists of an interesting combination of flat valley floor with desert scrub vegetation, punctuated by unusual rock formations (including the alligator-shaped ridge that gives rise to the area's name), and backdropped by the steeply rising Chuckwalla Mountains to the immediate south (not part of the landscape unit). Although there is a transmission line that passes through the landscape, it is to the south of most of the formations and blends effectively with the background when viewed from more distant viewpoints.	High	Interim	II	To retain the existing character of the landscape. The level of change to the characteristic landscape should be low. Management activities may be seen, but should not attract the attention of the casual observer. Any changes must repeat the basic elements of form, line, color, and texture found in the predominant natural features of the characteristic landscape.	Moderate The Proposed Project would parallel the existing DPV1 line to the north. Although the new structures would be the same design and height as the existing structures, the new structures would cause additional skylining and view blockage of the Chuckwalla Mountains beyond. The new line would also increase the structural complexity and industrial character visible from within the Alligator Rock ACEC. The resulting visual contrast for structural form and line would be moderate.	Not Consistent The moderate level of change would not meet the VRM Class II objective of a low degree of visual change. Also, the prominence of the additional line would attract the attention of the casual viewer.  While the new line would repeat characteristics of the existing DPV1 line, it would not repeat the basic elements of the existing natural features in the landscape.	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
KVP 11 Interstate 10 - Orocopia Mountains Proposed Project Figures D.3- 12A / 12B	View to the southeast toward existing DPV1 Towers 4423 and 4424X, from eastbound I-10, approximately 0.9 mile west of Hayfield Road.	Class C  This landscape unit encompasses portions of the Chuckwalla Valley extending from I-10 south to the Orocopia Mountains. The valley bottom and alluvial fans are flat and relatively non-descript with low growing grasses and shrubs. However, the southern portion of this landscape transitions into rugged foothills and ridges. While the visual variety of the landscape is enhanced by the variation in terrain characteristics, the overall scenic quality is compromised by the substantial presence of utility infrastructure including wood-pole utility lines and the lattice structure DPV1 transmission line.	High	Interim	III	To partially retain the existing character of the landscape. The level of change to the characteristic landscape should be moderate. Management Activities may attract attention but should not dominate the view of the casual observer. Changes should repeat the basic elements found in the predominant natural features of the characteristic landscape.	Low to Moderate  The Proposed Project would parallel the existing DPV1 line to the north. Although the new structures would be the same design and height as the existing structures, the new structures would cause additional skylining (extend above the horizon line) as the line crosses the lower ridges of the Orocopia Mountains. As a result, some additional view blockage of sky and mountains (though slight) would occur when viewed from Interstate 10. The new line would also increase the structural complexity and industrial character visible from I-10. The resulting visual contrast would be moderate for structural form and weak for line, color, and texture.	Consistent  The low to moderate level of change would meet the VRM Class III objective of a moderate (or lower) degree of visual change. While the new line would not repeat the basic elements of the existing natural features in the landscape, it would repeat the characteristics of the existing DPV1 line. Although the skylining aspect of thee new structures would result in increased prominence, at this viewing distance, the additional structures would not dominate the view of the casual observer.	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		BLM - EXI	STING VI	SUAL SE	TTING				BLM - VI	SUAL CO	ONTRAST A	NALYSIS			PACT FICANCE
Key	Description	Scenic Quality O	Naccification	Viewer			VRM Class			Level of Chan	ige	VDI	M Consisten	ov.	Before Mitigation	Mitigation
Viewpoint (KVP)	Description	Scenic Quanty C	Jiassification	Sensitivity	Status	Rating	Mana	gement Obj	ective	(See Appendix V Contrast Rating Work	R-2 sheets)	VKI	w Consistent	<b>cy</b>	After Mitigation	witigation
KVP 12 Cottonwood Springs Road - Joshua Tree National Park  Proposed Project  Figures D.3- 13A / 13B	View to the south-southeast toward existing DPV1 Towers 4349X through 4401, from Cottonwood Springs Road, just south of the entrance to Joshua Tree National Park.	Class This landscape unit encompas Shavers Valley. The valley be non-descript with low-growing more distant, rugged ridgeline the Orocopia Mountains define provide a backdrop to Shave lines transect both the north an with Interstate 10 running dow From the slightly elevated van distance of approximately two line is difficult to	sses the central portion of ottom is flat and relatively grasses and shrubs. The es (not part of the unit) of e much of the horizon and ers Valley. Transmission ad south sides of the valley on the center of the valley. Itage point of KVP 12 (at a miles), the existing DPV1	High	Interim	Ш	moderate. Mattract attenti the view of the should repeat the predomin	The level of stic landscape lanagement A on but should a casual observed	change to the should be ctivities may not dominate ver. Changes nents found in atures of the	Very Low The Proposed Project we the existing DPV1 line to However, from this viewing the structures would be discernable. The new would be the same design as the existing structures not attract the attention leaving Joshua Tree Nathough some addition blockage of the backgrofans and mountains would not be noticeable with the from Cottonwood Springs resulting visual contras weak.	o the north.  ng distance, be barely structures n and height s and would of viewers tional Park. nal view und alluvial uld occur, it when viewed s Road. The	The very low I the VRM Class (or lower) deg the new line v elements of th in the lands characteristics Also, at th additional effectively wi and would be	s III objective of	f a moderate range. While at the basic ral features repeat the p. DPV1 line. Ince, the lid blend rand terrain ratible to the	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
VIEW	POINT		CPUC - EX	ISTING V	ISUAL SI	ETTING				CI	PUC - VIS	SUAL CHAN	GE			PACT
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibilit	Distant	OT.	Duration		Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 13 Terra Lago in Indio Proposed Project Figures D.3-14A / 14B	View to the north toward existing DPV1 Towers 4236X through 4238X, from the Terra Lago golf and residential development in the City of Indio.	Moderate Foreground landscaped golf course with vibrant vegetative green coloration contrasting with the muted earth tones of the background hills and mountains. The existing DPV1 is a noticeable feature of industrial character. However, the lattice structures are able to blend somewhat with the background landforms, thereby reducing structural prominence.	High Residents of and visitors to the Terra Lago development anticipate a highly landscape environment that exhibits nature and designed vegetative characteristics. The introduction of any additional, noticeable industrial character or view blockage of the background mountains would be perceived an adverse visual change.	d ral On <b>High</b>	Foregrou	und Moder	ate Extended	High	Moderate to High	Structures 2236XX through 2238X of the DPV2 line would be built adjacent and slightly to the north of the existing DPV1 line and two other transmission lines. The DPV2 and DPV1 towers would appear similar in design and height. The DPV2 towers would be somewhat offset from the DPV1 towers and would cause a noticeable increase in structure prominence and industrial character. Additional view blockage of the background hills would also occur.		Co- Dominant	Moderate	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measures V-3 (Project Design) V-19 (Tower Painting)

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		BLM - EXI	STING VI	SUAL SE	TTING				BLM - VI	SUAL CO	NTRAST A	NALYSIS			PACT ICANCE
Key				Viewer			VRM Class			Level of Chan	ge	VD			Before Mitigation	
Viewpoint (KVP)	Description	Scenic Quality C	Siassification	Sensitivity	Status	Rating	Manag	gement Obje	ective	(See Appendix VR Contrast Rating Works		VKI	M Consistend	ey	After Mitigation	Mitigation
KVP 14 Coachella Valley Preserve  Proposed Project  Figures D.3- 15A / 15B	View to the south toward existing DPV1 Towers 4202 and 4203, from a hiking trail in the Coachella Valley Preserve, just west of Thousand Palms Canyon Road.	Not Avail	lable	High	Existing RMP  II  To retain the existing character of the landscape. The level of change to the characteristic landscape should be low. Management activities may be seen, but should not attract the attention of the casual observer. Any changes must repeat the basic elements of form, line, color, and texture found in the predominant natural features of the characteristic landscape.  VISUAL SETTING  Viewer Exposure					Low The Proposed Project wo the existing DPV1 line to Although the new structure the same design and hei existing DPV1 structures structures would cause adblockage of the backgmountains. The new line slightly increase the st complexity and industrial visible from the Coache Preserve. However, in the the three existing lattice transmission lines, the rescontrast would be ween the coache of the contract would be ween the contract when the contract would be ween the contract when the contract would be ween the contract would be ween the contract would be ween the contract when the contract would be ween the contract would be ween the contract when the contract we were the contract when the contract we were well as the contract when the contract we were well as the contract when the contract we were well as the contract when the contract we were well as the contract when the contract we were well as the contract when the contract we were well as the contract when the contract we were well as the cont	the north. es would be ght as the s, the new ditional view ground would also ructural character lla Valley e context of structure ulting visual	The low level VRM Class II of visual change not repeat the existing natura it would repeat existing three lines. Also, would not desired the existing three lines.	Consistent of change wou objective of a lo while the new he basic eleme at the character lattice tower to the additional s ominate the vie attention of, the observer.	ow degree of v line would ents of the e landscape, istics of the ansmission structures ew of, nor	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
VIEW	POINT		CPUC - EX	ISTING V	VISUAL SETTING					СР	UC - VIS	UAL CHAN	GE			PACT ICANCE
					Vi	iewer Expo	sure		-						Before	
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Distance Zone	Number of Viewer	of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Mitigation ——— After Mitigation	Mitigation
KVP 15 State Route 62 Scenic Hwy. Proposed Project Figures D.3- 16A / 16B	View to the south-southeast toward proposed tower location 207, from southbound SR 62, just north of the crossing of SR 62.	Low-to-Moderate Foreground to middleground flat, desert landform dominated by a profusion of energy infrastructure consisting of the predominantly vertical forms of wind turbines and electric transmission line towers. This industrial-appearing landscape is backdropped by Mount San Jacinto, rising dramatically from the desert floor.	High SR 62 is a State designated Scenic Highway and therefore warrants a high rating for viewer concern. Although travelers on this short stretch of SR 62 would not likely notice the change in conductors and tower configurations proposed for the DPV1 corridor, any perceived increase in industrial character, structure prominence, or view blockage would be experienced as an adverse visual impact.	High	Distance		Moderate to Extended	High	Moderate to High	Tower M1-T1 would be reconductored. Tower M61-T2 would be removed. Tower T266 would be replaced with a taller lattice structure. Although the replacement tower would appear similar in design and height to that of Tower M1-T1, the increased height over the existing tower would cause additional skylining (extending above the horizon), view blockage (of sky), and increased structural prominence,	Moderate	Co- Dominant	Low to Moderate	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		CPUC - EXI	STING V	ISUAL SET	TING				СР	UC - VIS	UAL CHAN	GE			PACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Vie Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity		Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 16 Painted Hills Road  Proposed Project  Figures D.3- 17A / 17B	View to the south-southeast toward proposed tower location 209, from Painted Hills Road, just east of Country View Road.	Low-to-Moderate Foreground to middleground flat, desert landform dominated by a profusion of energy infrastructure consisting of the predominantly vertical forms of wind turbines and electric transmission line towers. A background of distant hills and mountains low on the horizon adds visual interest. Mount San Jacinto is the dominant natural feature in the region.	High Residential viewers in the Painted Hills Road neighborhood would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky, ridges, and Mount San Jacinto) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Tower M1-T3 would be reconductored. Tower M61-T4 would be removed. Tower T262 would be replaced with a taller lattice structure. Although the replacement tower would appear similar in design and height to that of Tower M1-T3, the increased height over the existing tower would result in increased skylining, view blockage, and structural prominence, resulting in increased visual contrast.	Moderate	Co- Dominant	Low to Moderate	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
KVP 17 Whitewater Canyon Road Proposed Project Figures D.3- 18A / 18B	View to the southeast toward proposed tower location 215, from Whitewater Canyon Road, south of Bonnie Bell.	Moderate Foreground desert river canyon landscape defined by low canyon walls and the vertical, industrial forms of wind turbines, backdropped by the massive angular form of Mount San Jacinto, rising dramatically from the flat desert floor.	High Travelers on Whitewater Canyon Road, including residents from the nearby residential community of Bonnie Bell, would consider any increase in industrial character or built structural prominence in the canyon, or view blockage of the background sky and Mount San Jacinto an adverse visual change.	High	Foreground	Low to Moderate	Moderate	Moderate to High	Moderate to High	Tower M3-T1 would be reconductored. Tower M63-T2 would be removed. Tower T251 would be replaced with a taller lattice structure. The replacement tower would appear similar in design and height to that	Low to Moderate	Subordinate to Co- Dominant	Low	Low to Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	/POINT		CPUC - EXI	STING V	ISUAL SET	TING				СР	UC - VIS	UAL CHAN	GE			PACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	View Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 18  Haugen- Lehmann Way West Palm Springs Village  Proposed Project  Figures D.3- 19A / 19B	View to the west toward proposed tower location 226, from Haugen- Lehmann Way, just south of the intersection with Amethyst Drive, in West Palm Springs Village.	Low to Moderate Foreground rural residential desert landscape dominated by the vertical forms of utility poles and electric transmission line towers, and backdropped by a low range of rolling hills and angular ridges with muted earth-tone colors.	High Although energy transmission infrastructure features prominently in the landscape visible within this community, residential viewers would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky, ridges, or Mount San Jacinto if viewing to the south) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Replacement of the existing wood-pole H-frame structure (T231) with a new lattice tower (226) would result in increased structural complexity and industrial character, which would cause an increase in visual contrast.	Moderate	Co- Dominant	Low to Moderate	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	<b>Measure</b> V-3 (Project Design)
KVP 19 Morongo Community Center  Proposed Project  Figures D.3- 20A / 20B	View to the southwest toward proposed tower location 256, from the Morongo Community Center at 13000 Fields Road, north of I-10.	Low to Moderate Foreground dominated by the flat arid landscape of San Gorgonio Pass with prominent energy transmission infrastructure (towers and conductors), paved parking surfaces, and Interstate 10 immediately to the south, and backdropped by steeply rising ridges both to the north and south of the Pass.	High Although energy transmission infrastructure features prominently in the foreground landscape when viewed from the Community Center, visitors to the Community Center would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky, ridges, and Mount San Jacinto) an adverse visual change.	High	Foreground	Low to Moderate	Extended	High	Moderate to High	Tower M14-T1 would be reconductored. Tower M74-T2 would be removed. Towers T173 and T174 would be replaced with taller lattice structures. Although the replacement towers would appear similar in design and height to that of Tower M14-T1, the increased height over the existing H-frames would result in increased skylining, view blockage (of sky), structural prominence, and industrial character resulting in increased visual contrast, which would be somewhat offset by the net reduction in the number of structures.	Moderate	Co- Dominant	Low to Moderate	Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

S-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		CPUC - EXI	STING V	ISUAL SET	TING				СР	UC - VIS	UAL CHAN	GE			PACT FICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Vier Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 20 Murray Street in Banning Proposed Project Figures D.3- 21A / 21B	View to the northeast toward proposed tower locations 102 and 103, from Murray Street in the City of Banning.	Low to Moderate  Semi-arid rural residential landscape with minimal visual variety, dominated by the nearby grass- and shrub- covered hills and ridges with muted hues of tans and yellows with some darker contrasting greens from within residential yards. Existing vertical forms of energy infrastructure (lattice and wood-pole structures) with industrial character are prominent, particularly where structure skylining occurs (structures extending above the horizon line).	High  Although energy transmission infrastructure features prominently in the foreground landscape at the base of the hills, residents would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky or hills) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Tower M17-T1 would be reconductored. Tower M77-T1 would be removed. Towers T152 and T153 would be replaced with taller lattice structures. Although the replacement towers would appear similar in design and height to that of Tower M17-T1, the increased height over the existing H-frames would result in increased skylining. However, the lattice design would allow the structures to better blend with the background.	Low to Moderate	Co- Dominant	Low to Moderate	Low to Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design
KVP 21 Cedar Hollow Road in Beaumont Proposed Project Figures D.3- 22A / 22B	View to the west-southwest toward proposed tower locations 127 and 128, from Cedar Hollow Road, in the City of Beaumont.	Low to Moderate Foreground suburban residential landscape of one and two-story single-family homes, dominated by an adjacent energy transmission infrastructure (towers and conductors) corridor. Generally lacking distinctive features or elements of visual interest.	High  Although energy transmission infrastructure features prominently in the foreground of views from the adjacent neighborhood, residents would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Towers M22-T4 and M23-T1 would be reconductored. Lattice Towers M82-T4 through M83-T2 would be removed. H-frame Towers T114 and T115 would be replaced with taller lattice structures, which would be of similar design and height as the existing lattice towers to	Low	Reduced	Reduced	Improved	BEFORE: Beneficial (Class IV) AFTER: Same (Improved)	<b>Measure V-3</b> (Project Design

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEWPOINT			CPUC - EX	ISTING V	ISUAL SET	TING				CPUC - VISUAL CHANGE					IMPACT SIGNIFICANCE		
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Vie Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation	
KVP 22 Stargazer St. and Rose Ave. in Beaumont Proposed Project Figures D.3- 23A / 23B	View to the east- southeast toward proposed tower locations 129 and 130, from the intersection of Stargazer Street and Rose Avenue in the City of Beaumont.	Moderate Foreground new suburban residential landscape of onestory single-family homes. Prominent (though partially screened) energy transmission infrastructure (towers and conductors) is adjacent and to the rear of the southern perimeter of the development. Generally lacking distinctive features or elements of visual interest.	High Although energy transmission infrastructure features prominently in the foreground of views from the adjacent neighborhood, residents would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Towers M24-T1 and M23-T3 would be reconductored. Lattice Towers M83-T3 and M84-T1 would be removed. H-frame Towers T105 through T107 would be replaced with fewer, taller lattice structures, which would be of similar design and height as the existing lattice towers to be reconductored. Tower replacement would eliminate the visually prominent H-frame structures and their asynchronous spans (relative to the reconductored lattice towers). The result would be reduced structural prominence and complexity and industrial character within the corridor.	Low	Reduced	Reduced	Improved	BEFORE: Beneficial (Class IV)  AFTER: Same (Improved)	<b>Measure</b> V-3 (Project Design)	
KVP 23 Oak Valley Golf Course Proposed Project Figures D.3- 24A / 24B	View to the east toward proposed tower locations 130 and 131, from the Oak Valley Golf Course in the City of Beaumont.	Moderate Foreground, manicured landscape of grass and trees designed to provide open views and aesthetic appeal for recreational visitors. Adjacent residential development newly constructed. Existing electric transmission facilities of various designs impart prominent industrial character.	High Visitors to the golf course expect to see a landscape with high aesthetic appeal, characterized by a mosaic of natural and managed vegetative forms. Any additional intrusion of built structures with industrial character or blockage of views from any of the golf course grounds would be seen as an adverse visual change.	High	Foreground	Low to Moderate	Extended	Moderate to High	Moderate to High	Towers M24-T1 and M24-T2 would be reconductored. Lattice Towers M84-T1 and M84-T2 would be removed. H-frame Towers T104 through T106 would be replaced with fewer, taller lattice	Low	Reduced	Reduced	Improved	BEFORE: Beneficial (Class IV)  AFTER: Same (Improved)	Measure V-3 (Project Design)	

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		CPUC - EXI	STING V	ISUAL SET	TING				CPUC - VISUAL CHANGE						IMPACT SIGNIFICANCE	
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Distance Zone	Number of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation	
KVP 24 Pilgrim Road in San Timoteo Canyon  Proposed Project  Figures D.3- 25A / 25B	View to the west-southwest toward proposed tower locations 183 and 184, from Pilgrim Road, off of San Timoteo Canyon Road in San Timoteo Canyon.	Moderate Rural residential landscape of rolling grass-covered hills with minimal visual variety, and the prominent complex vertical forms of energy transmission infrastructure. Lattice structures blend effectively with background landforms but become noticeably more conspicuous where structure skylining occurs (structures extending above the horizon line).	High  Although energy transmission infrastructure features prominently in the foreground landscape, residents would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky or ridges) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Tower M38-T2 would be reconductored. Lattice Tower M98-T2 would be removed. H-frame Towers T28 and T29 would be replaced with taller lattice structures, which would be of similar design and height as the existing lattice towers to be reconductored. The result would be reduced structural complexity and industrial character within the corridor, but with slightly more prominent conductors.	Low	Co- Dominant	Low	Low to Moderate	BEFORE: Beneficial (Class IV)  AFTER: Same (Improved)	Measure V-3 (Project Design)	
KVP 25 Canyon Vista Dr. and Chase Canyon Lane in Colton Proposed Project Figures D.3- 26A / 26B	View to the west toward existing Towers M42-T2 and M42-T3, from the intersection of Canyon Vista and Chase Canyon Lane in the City of Colton.	Moderate Foreground residential landscape consisting of newer two-story, single-family residences with some established trees providing interesting color contrasts with red-tiled roofs. Backdropped by grass-covered rolling hills with monotone tan grasses, punctuated by structurally complex, lattice transmission towers with substantial skylining.	High Although energy transmission infrastructure features prominently in the foreground views from the residential neighborhood, residents would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky or ridges) an adverse visual change.	High	Foreground	Low	Extended	Moderate to High	Moderate to High	Towers M42-T2 and M42-T3 would be reconductored. The result would be slightly more prominent conductors on the Devers-Vista No. 1 and No 2 structures with slightly increased visual contrast and view blockage.	Low	Co- Dominant	Low	Low to Moderate	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	<b>Measure</b> V-3 (Project Design)	
KVP 26 Right of Way Park off Beaumont Ave. in Loma Linda Proposed Project Figures D.3- 27A / 27B	View to the north toward existing Towers M2-T4, from a bench at the top of the right of way park, adjacent to Beaumont Avenue in the City of Loma Linda.	Low to Moderate Foreground to middleground suburban electric utility corridor with substantial industrial character, but hosting developed park facilities within the right of way. Vegetation within, and adjacent to the corridor provides visual interest and color contrast but is dominated by the larger, complex industrial forms of the transmission structures.	High  Although energy transmission infrastructure dominates foreground views from the park areas within the corridor, from adjacent residential neighborhoods, and from roads that cross the right of way, viewers would consider any increase in industrial character, structure prominence, or view blockage of higher value landscape features (background sky or mountains) an adverse visual change.	High	Foreground	Moderate	Extended	High	Moderate to High	The existing lattice structures would have the outside circuits reconductored, which would then match the bundled, inside circuits along the center-line of the right of way. The result would be slightly more prominent conductors and slightly increased view blockage.	Low	Subordinate	Low	Low	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	<b>Measure</b> V-3 (Project Design)	

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	/POINT	BLM - E	XISTING V	ISUAL SE	BLM - VISUAL CO		PACT ICANCE			
Key	Description	Samia Quality Classification	Viewer			VRM Class	Level of Change	VDM Consistency	Before Mitigation	Mitigation
Viewpoint (KVP)	Description	Scenic Quality Classification	Sensitivity	Status	Rating	Management Objective	(See Appendix VR-2 Contrast Rating Worksheets)	VRM Consistency	After Mitigation	Mitigation
KVP 27 Eagletail Mountains Courthouse Rock Harquahala- West Alternative Figures D.3- 28A / 28B	View to the east- northeast across Harquahala Plain toward Big Horn Mountain, from BLM Road YE013 to Courthouse Rock, east of the Eagletail Mountains.	Not Available	Not Available	Existing RMP	III	To partially retain the existing character of the landscape. The level of change to the characteristic landscape should be moderate. Management Activities may attract attention but should not dominate the view of the casual observer. Changes should repeat the basic elements found in the predominant natural features of the characteristic landscape.	Moderate to High The Harquahala-West Alternative would result in the introduction of a new transmission line into a natural appearing landscape lacking similar built structures of industrial character. The resulting structural form and line contrast would be strong and the color contrast would be weak to moderate.	Not Consistent  The moderate to high level of change would not meet the VRM Class III objective of a moderate degree of visual change. The new line would not repeat the basic elements of the existing natural features in the landscape. The line would cause view blockage of background sky, distant mountain ranges, and Harquahala Plain, and would dominate the views of the casual observer.	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)
KVP 28 Salome Highway Saddle Mountain Palo Verde Alternative Figures D.3- 29A / 29B	View to the south-southwest toward Palo Verde Alternative tower locations D-123 through D-125 and Saddle Mountain, from Salome Highway, approximately 1.2 miles east of the highway crossing.	Not Available	Not Available	Existing RMP	III	To partially retain the existing character of the landscape. The level of change to the characteristic landscape should be moderate. Management Activities may attract attention but should not dominate the view of the casual observer. Changes should repeat the basic elements found in the predominant natural features of the characteristic landscape.	Low  The Palo Verde Alternative would parallel the existing DPV1 line to the west. Although the new structures would be the same design and height as the existing DPV1 structures, the new structures would cause some additional view blockage of Saddle Mountain in the background. While the new line would slightly increase the structural complexity and industrial character visible from Salome Highway, it would also blend substantially with the background landform. In the context of the two existing lattice structure transmission lines, the resulting visual contrast would be weak.	Consistent The low level of change would meet the VRM Class III objective of a moderate (or lower) degree of visual change. While the new line would not repeat the basic elements of the existing natural features in the landscape, it would repeat the characteristics of the existing two lattice tower transmission lines. Also, the additional structures would not dominate the view nor attract the attention of the casual observer.	BEFORE: Adverse but Less Than Significant (Class III)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)

### METHODOLOGIES:

BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT		CPUC - E	XISTING V	ISUAL SE	TTING				CPUC - VISUAL CHANGE						ACT ICANCE
Key Viewpoint (KVP)	Description	Visual Quality	Viewer Concern	Visibility	Distance Zone	Numbe of Viewers	Duration of View	Overall Viewer Exposure	Overall Visual Sensitivity	Description of Visual Change	Visual Contrast	Project Dominance	View Blockage	Overall Visual Change	Before Mitigation ————————————————————————————————————	Mitigation
KVP 29 Harquahala Junction Switchyard Alternative Figure D.3-30	View to the southeast toward the alternative substation site, from Salome Highway, at mile marker 39.	Low to Moderate Foreground flat desert landscape with horizontal form. Backdropped by rounded to angular hills and mountains with jagged ridgelines. Natural vegetation is of subdued yellow and green colors. Prominent, skylined foreground transmission line structures of tubular and lattice design, exhibit industrial character and compromise landscape coherence and overall visual quality.	High  Although energy transmission infrastructure features prominently in the foregroun views from Salome Highway travelers would consider an increase in industrial character, structure prominence, or view blockag of higher value landscape features (background sky o mountains) an adverse visua change.	d /, / / High	Foreground	Low to Moderat	PANADA	Moderate to High	Moderate to High	Placement of a 500 kV switchyard immediately adjacent to Salome Highway would introduce substantial industrial character, visual contrast and view blockage into views from Salome Highway.	Moderate to High	Co- Dominant	Moderate	Moderate	BEFORE: Significant (Class II)  AFTER: Less Than Significant	Measures V-6a to V-6c (Surface Treatment, Screening, and Lighting) V-35 (Screening)
VIEW	POINT		BLM - EX	ISTING VI	SUAL SE	TTING				BLM - VISUAL CONTRAST ANALYSIS					IMPACT SIGNIFICANCE	
Key Viewpoint	Description	Scenic Quality Classification		Viewer	VRM Class					Level of Change		VRI	M Consisten	CV	Before Mitigation	Mitigation
(KVP)	2 decinpatent	Coomo Quanty C		Sensitivity	Status	Rating	Management Objective		(See Appendix VR-2 Contrast Rating Worksheets)		Tim Consistency			After Mitigation	, maganon	
KVP 30 Eastbound I-10 at Alligator Rock  Desert Southwest Transmission Project & Alligator Rock South of I-10 Frontage Alternatives  Figures D.3- 31A / 31B	View to the east toward the Desert Southwest Transmission Project and Alligator Rock South of I-10 Alternatives, from eastbound I-10, approximately one mile west of the Desert Center off-ramp.	Class B  The landscape consists of an interesting combination of flat valley floor with desert scrub vegetation, punctuated by unusual rock formations and the alligator-shaped ridge that gives rise to the area's name. The rugged, steeply rising Chuckwalla Mountains provide a backdrop to the immediate south (not part of the landscape unit). A wood-pole utility line and fence line are visible in the foreground of views from I-10 though they are not prominent relative to Alligator Rock.		High	Interim	II	landscape. characteristic Management	attract the atter r. Any change ents of form, li in the predom	nange to the sould be low. be seen, but ntion of the es must repeat ine, color, and ninant natural	generally lacking similar built structures of industrial character. Although the DPV1 line passes through the ACEC, it is sufficiently to the south to not appear noticeable in views from Interstate 10. Also, the new line would cause substantial view		Rock and would appear co-dominant to the casual observer.		BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	Measure V-3 (Project Design)	

### METHODOLOGIES:

VRM BUREAU OF LAND MANAGEMENT LANDS: VISUAL RESOURCE MANAGEMENT (VRM)

VS-VC Non-BLM Lands: Visual Sensitivity - Visual Change (VS-VC)

VIEW	POINT	BLM - E	XISTING V	SUAL SE	TTING		BLM - VISUAL CO		PACT	
Key Viewpoint	Description	Scenic Quality Classification	Viewer			VRM Class	Level of Change	VRM Consistency	Before Mitigation	Mitigation
(KVP)	Description	Scenic Quanty Classification	Sensitivity	Status	Rating	Management Objective	(See Appendix VR-2 Contrast Rating Worksheets)	VKW Consistency	After Mitigation	Willigation
KVP 31 Southbound Kaiser Road  Alligator Rock - North Of Desert Center Alternative  Figures D.3- 32A / 32B	View to the south toward the Alligator Rock North of Desert Center Alternative, from southbound Kaiser Road, approximately one mile north of I-10 and Desert Center	Class C  The landscape north of I-10 is within the central portion of Chuckwalla Valley and is flat and relatively non-descript with low growing grasses and shrubs, and backdropped by the Chuckwalla Mountains to the south. Closer to Desert Center, scenic quality becomes more influenced by a number of built structures that are in a state of disrepair.	High	Interim	III	To partially retain the existing character of the landscape. The level of change to the characteristic landscape should be moderate. Management Activities may attract attention but should not dominate the view of the casual observer. Changes should repeat the basic elements found in the predominant natural features of the characteristic landscape.	Moderate to High The Alligator Rock-North of Desert Center Alternative would result in the introduction of a new transmission line into a rural landscape lacking similar built structures of industrial character. Although other built structures are visible in the Desert Center landscape, only a single telecommunications tower shares the structural complexity or vertical extent of the lattice transmission towers. The resulting structural form and line contrast would be moderate to strong, color contrast would be weak to moderate, and texture contrast would be weak.	Not Consistent  The moderate to high level of change would not meet the VRM Class III objective of a moderate (or lower) degree of visual change. The new transmission line would not repeat the basic elements of the existing natural features in the landscape. Also, the new line would cause view blockage of portions of the background Chuckwalla Mountains and would appear co-dominant to the casual observer.	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	<b>Measure</b> V-3 (Project Design)
KVP 32 Westbound I-10 at Alligator Rock Alligator Rock-Blythe Energy Transmission Alternative Figures D.3- 33A / 33B	View to the southwest toward the Alligator Rock-Blythe Energy Transmission Alternative adjacent to Alligator Rock, from westbound I-10, approximately 0.72 mile east of the Desert Center overpass.	Class B  The landscape consists of an interesting combination of flat valley floor with desert scrub vegetation, punctuated by unusual rock formations (including the alligator-shaped ridge that gives rise to the area's name), and backdropped by the steeply rising Chuckwalla Mountains to the immediate south (not part of the landscape unit). Although there is a transmission line that passes through the landscape, it is to the south of most of the formations and blends effectively with the background.	High	Interim	II	To retain the existing character of the landscape. The level of change to the characteristic landscape should be low. Management activities may be seen, but should not attract the attention of the casual observer. Any changes must repeat the basic elements of form, line, color, and texture found in the predominant natural features of the characteristic landscape.	Moderate to High The Alligator Rock-Blythe Energy Transmission Alternative would result in the introduction of a new transmission line into a landscape generally lacking similar built structures of industrial character. Although the DPV1 line passes through the ACEC, it is sufficiently to the south to not appear noticeable in views from Interstate 10. Also, the new line would cause substantial view blockage of Alligator Rock when viewed by westbound travelers on I- 10. The resulting structural form and line contrast would be strong and the color and texture contrast would be weak.	Not Consistent The moderate to high level of change would not meet the VRM Class II objective of a low degree of visual change. The new transmission line would not repeat the basic elements of the existing natural features in the landscape. Also, the new line would cause substantial view blockage of Alligator Rock and would appear co-dominant to the casual observer.	BEFORE: Significant (Class I)  AFTER: Same (Impact Reduced)	<b>Measure</b> V-3 (Project Design)