PACIFIC GAS AND ELECTRIC COMPANY Embarcadero-Potrero 230 kV Transmission Project NTP # 1 Potrero Site Preparation Submittal

APM or MM addressed:	APM AQ-1. Minimize Fugitive Dust.
Attachments:	None
Date Submitted:	Sept 04, 2014, 2014

APM AQ-2. Minimize Fugitive Dust.

Consistent with Table 2 of the [1999] BAAQMD CEQA Guidelines, PG&E will minimize dust emissions during construction by implementing the following measures:

- Water all active construction areas at least twice daily.
- Cover all trucks hauling soil, sand, and other loose materials or require all trucks to maintain at least two feet of freeboard.
- Pave, apply water three times daily, or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites.
- Sweep daily (with water sweepers) all paved access roads, parking areas, and staging areas at construction sites.
- Sweep streets daily (with water sweepers) if visible soil material is carried onto adjacent public streets.
- Post a publicly visible sign with the telephone number and person to contact regarding dust complaints. This person
 will respond and take corrective action within 48 hours. The BAAQMD's phone number will also be visible to ensure
 compliance with applicable regulations.

Note that implementation of the first measure listed above would not apply to paved areas with no exposed soil or when rains are occurring.

PG&E response:

The City of San Francisco requires watering three times per shift in Maher Ordinance areas with contaminated soils. As a result, the following Fugitive Dust Control Plan will apply in areas without an approved Asbestos Dust Mitigation Plan (ADMP).

- Water all active construction areas three times per active work shift (a shift is 8 hours).
- Cover all trucks hauling soil, sand, and other loose materials or require all trucks to maintain at least two feet of freeboard.
- Pave, apply water three times per shift, or apply (non-toxic) soil stabilizers on all unpaved access roads, parking areas, and staging areas at construction sites.
- Sweep daily (with water sweepers) all paved access roads, parking areas, and staging areas at construction sites.
- Sweep streets daily (with water sweepers) if visible soil material is carried onto adjacent public streets.
- Post a publicly visible sign with the telephone number and person to contact regarding dust complaints. This person will respond and take corrective action within 48 hours. The BAAQMD's phone number will also be visible to ensure compliance with applicable regulations.

Note that implementation of the first and third measures listed above would not apply to paved areas with no exposed soil or when rains are occurring.