

TOM C. DYKE drilling • blasting

PHONE 619-445-2270
FAX 619-445-4934

P.O. BOX 352, ALPINE, CALIFORNIA 91903

February 19, 2011

Steve Fitzwilliam
Geosyntec Consultants
10875 Rancho Bernardo Road, Suite 200
San Diego, California 92127

Re: SDG&E Suncrest Substation – Site Specific Blast Plan

Project blasting that is done at the SDG&E Suncrest Substation pad facilities will conform to the following:

The Contractor will obtain all necessary state and local permits prior to the commencement of blasting operations.

The Contractor will employ a state licensed blaster to conduct all blasting operations.

The Contractor will conduct all blasting operations in accordance with the State of California Construction Safety Orders.

The Contractor will not store explosives on site.

The Contractor will notify SDG&E, two working days before each shot with the anticipated time of blasting. Matt Huber (619-787-9517) mhuber@semprautilities.com.

The contractor to notify Beta Engineering two working days prior to each shot with the anticipated time of blasting. Brian Donald (858-750-2370) brian.donald@betaengineering.com

The contractor will notify Geosyntec Consultants two days before each shot with the anticipated time of blasting. Steven Fitzwilliam (858-674-6559) sfitzwilliam@geosyntec.com

The Contractor will make and document a pre-blast survey of SDG&E facilities located within 300 feet of the blasting site, and preblast notification when facilities are within 600 feet of the blast site.

The Contractor will monitor all blasting operations with a Nomis NCSC 5400 portable seismograph. Seismograph monitoring will be located at the nearest SDG&E structure within 600 feet of the blast site. Results shall be submitted to SDG&E for review.

The Contractor will provide for limiting the maximum peak particle velocity at the nearest point to the SDG&E facilities, 5 inches per second at SDG&E gas pipelines, 4 inches per second at electrical power poles and lattice towers.

TOM C. DYKE drilling • blasting

PHONE 619-445-2270
FAX 619-445-4934

P.O. BOX 352, ALPINE, CALIFORNIA 91903

Location of blasting (see attached map)

Pad excavation has begun. Non-rippable conditions have been encountered near the top of the easterly slope of the substation pad. Blasting will be required to facilitate excavation.

Blast holes will be 4 inches in diameter, 10-21 feet in depth, hole pattern is 9 feet by 9 feet, hole inclination is vertical. Explosives will be Semi-gelatin dynamite, Cast Boosters and ANFO. The blast area is near no SDG&E facilities. The nearest structure to project blasting is approximately 3,500 feet south. No Project personnel within 800 feet of blast site. The typical hole load is as follows:

Single deck holes with one cartridge of 2x8 semigelatin dynamite or 14oz cast boosters and ANFO in amounts not to exceed a scaled distance factor of 55 or greater.

Blast hole stemming height will be 7-12 feet. The number of blast holes will be 112. Maximum pounds per delay will be a 55 scaled distance factor or greater.

The material to be blasted is granitic rock.

The Contractor will review seismic records and blasters log after each blast to insure that particle velocity limits are met.

If you have any questions or require additional information, please contact the undersigned.

TOM C. DYKE DRILLING & BLASTING, INC.
California Contractors License Number 542984


Mike Burkett

**SAN DIEGO GAS & ELECTRIC SUNCREST SUBSTATION
SITE SPECIFIC BLASTING PLAN**

NAME OF CONTRACTOR
Tom Dyke Drilling & Blasting, Inc.

BLAST IDENTIFICATION NUMBER
SC-2

LOCATION
SC-2 See attached drawing

DATE TIME OF BLAST
Wednesday 02-23-11 @ 12:10-1:00 P.M.

TYPE OF MATERIAL BLASTED
Granitic Rock

NUMBER OF HOLES
112

BURDEN AND SPACING
9 feet x 9 feet

DIAMETER OF HOLES
4 inch

DEPTH OF HOLES
10-21 feet (see attached hole depth on shot map)

HEIGHT OF STEMMING
7-12 feet

TYPES OF EXPLOSIVES USED
ANFO, Packaged Emulsion (Dyno AP), Semi - Gelatin Dynamite (Unigel) & Cast Boosters

TYPE OF CAPS USED
Non Electric – Nonel MS & Nonel EZTL

DELAY PERIOD
17ms, 175ms, 475ms and 500ms

PROPOSED AMOUNT OF EXPLOSIVES
2268 Pounds

MAXIMUM AMOUNT OF EXPLOSIVES PER DELAY PERIOD OF 08 MILLISECONDS OR GREATER
65 pounds

POWDER FACTOR
0.77

METHOD OF FIRING
Non Electric mushroom starter

TYPE OF CIRCUIT
Non Electric- Shock Tube

WEATHER CONDITIONS
N/A

WIND DIRECTION
N/A

DIRECTION AND DISTANCE TO NEAREST STRUCTURE OF CONCERN
None within ½ mile

TYPE OF INSTRUMENTATION
Nomis NCSC 5400 portable seismograph

VIDEO RECORDING
Yes

LOCATION AND PLACEMENT OF INSTRUMENTS
Water well 600 feet south

TRAFFIC CONTROL
Guards at all access points to the blast area, no public or job site personnel within 800 feet

INSTRUMENTATION RECORDS

ANY UNUSUAL CIRCUMSTANCES OR OCCURANCES DURING BLAST

MEASURES TAKEN TO LIMIT AIR NOISE AND FLY ROCK
Proper blast design, stemming height and materials.

BLASTER
AJ Corirossi

Area SC-2


112 Holes

Hole Diameter 4 inch


Pattern 9' x 9'

10 Feet min. hole depth


23870 Stake



23876 Stake



TOM C. DYKE
DRILLING & BLASTING
POST OFFICE BOX 352
ALPINE, CALIFORNIA 91903



Scale
1 inch = 30 feet

(E) 46
TYP

(E) 45
D.8
TYPE F CB

(D) 48

(E) 41
TYP
"8" TEE
JOINT

(E) 45
TYP
RESTRAINED JOINT
L=160
9048.68
4726.03

3240 FG 2.0%
3200 FG
3190 FG
3180 FG
3170 FG
3160 FG
3150 FG
3140 FG
3130 FG
3120 FG
3110 FG
3100 FG
3090 FG
3080 FG
3070 FG
3060 FG
3050 FG
3040 FG
3030 FG
3020 FG
3010 FG
3000 FG
2990 FG
2980 FG
2970 FG
2960 FG
2950 FG
2940 FG
2930 FG
2920 FG
2910 FG
2900 FG
2890 FG
2880 FG
2870 FG
2860 FG
2850 FG
2840 FG
2830 FG
2820 FG
2810 FG
2800 FG
2790 FG
2780 FG
2770 FG
2760 FG
2750 FG
2740 FG
2730 FG
2720 FG
2710 FG
2700 FG
2690 FG
2680 FG
2670 FG
2660 FG
2650 FG
2640 FG
2630 FG
2620 FG
2610 FG
2600 FG
2590 FG
2580 FG
2570 FG
2560 FG
2550 FG
2540 FG
2530 FG
2520 FG
2510 FG
2500 FG
2490 FG
2480 FG
2470 FG
2460 FG
2450 FG
2440 FG
2430 FG
2420 FG
2410 FG
2400 FG
2390 FG
2380 FG
2370 FG
2360 FG
2350 FG
2340 FG
2330 FG
2320 FG
2310 FG
2300 FG
2290 FG
2280 FG
2270 FG
2260 FG
2250 FG
2240 FG
2230 FG
2220 FG
2210 FG
2200 FG
2190 FG
2180 FG
2170 FG
2160 FG
2150 FG
2140 FG
2130 FG
2120 FG
2110 FG
2100 FG
2090 FG
2080 FG
2070 FG
2060 FG
2050 FG
2040 FG
2030 FG
2020 FG
2010 FG
2000 FG
1990 FG
1980 FG
1970 FG
1960 FG
1950 FG
1940 FG
1930 FG
1920 FG
1910 FG
1900 FG
1890 FG
1880 FG
1870 FG
1860 FG
1850 FG
1840 FG
1830 FG
1820 FG
1810 FG
1800 FG
1790 FG
1780 FG
1770 FG
1760 FG
1750 FG
1740 FG
1730 FG
1720 FG
1710 FG
1700 FG
1690 FG
1680 FG
1670 FG
1660 FG
1650 FG
1640 FG
1630 FG
1620 FG
1610 FG
1600 FG
1590 FG
1580 FG
1570 FG
1560 FG
1550 FG
1540 FG
1530 FG
1520 FG
1510 FG
1500 FG
1490 FG
1480 FG
1470 FG
1460 FG
1450 FG
1440 FG
1430 FG
1420 FG
1410 FG
1400 FG
1390 FG
1380 FG
1370 FG
1360 FG
1350 FG
1340 FG
1330 FG
1320 FG
1310 FG
1300 FG
1290 FG
1280 FG
1270 FG
1260 FG
1250 FG
1240 FG
1230 FG
1220 FG
1210 FG
1200 FG
1190 FG
1180 FG
1170 FG
1160 FG
1150 FG
1140 FG
1130 FG
1120 FG
1110 FG
1100 FG
1090 FG
1080 FG
1070 FG
1060 FG
1050 FG
1040 FG
1030 FG
1020 FG
1010 FG
1000 FG
990 FG
980 FG
970 FG
960 FG
950 FG
940 FG
930 FG
920 FG
910 FG
900 FG
890 FG
880 FG
870 FG
860 FG
850 FG
840 FG
830 FG
820 FG
810 FG
800 FG
790 FG
780 FG
770 FG
760 FG
750 FG
740 FG
730 FG
720 FG
710 FG
700 FG
690 FG
680 FG
670 FG
660 FG
650 FG
640 FG
630 FG
620 FG
610 FG
600 FG
590 FG
580 FG
570 FG
560 FG
550 FG
540 FG
530 FG
520 FG
510 FG
500 FG
490 FG
480 FG
470 FG
460 FG
450 FG
440 FG
430 FG
420 FG
410 FG
400 FG
390 FG
380 FG
370 FG
360 FG
350 FG
340 FG
330 FG
320 FG
310 FG
300 FG
290 FG
280 FG
270 FG
260 FG
250 FG
240 FG
230 FG
220 FG
210 FG
200 FG
190 FG
180 FG
170 FG
160 FG
150 FG
140 FG
130 FG
120 FG
110 FG
100 FG
90 FG
80 FG
70 FG
60 FG
50 FG
40 FG
30 FG
20 FG
10 FG
0 FG