

ASSUMPTIONS FOR AIR QUALITY AND NOISE ANALYSES
Tionesta 3R

- Area to be graded for 3R facilities = 0.37 acres include area for building and equipment yard plus 10 foot perimeter band.
- Width of grading for 12-foot wide gravel-covered access road = 20 feet.
Length of road = 1000 feet.
Area of grading for road = 20,000 square feet = 0.46 acre.
- Two 1-foot wide fiber optic trenches are excavated between the building in the fenced compound and the property line. The maximum combined trenching distance is 1000 feet.
- Specialized construction workers commute to site the number of days required for each activity (e.g., site grading).
- General construction workers commute to site for sum of days required for set of activities.
- Wind erosion conservatively assumed to affect sum of disturbed site areas during sum of days needed for grading, trenching, utility installation, and access road construction, but not for days used to construct pads and place shelters. The emission factor is derived Attachment A.
- Fugitive dust from travel of construction vehicles over site, including access road, is included in emission factor of 39.4 pounds of PM10 per day per acre of construction activity area. This emission factor is conservatively applied to the total time for activities associated with preparation and construction of the pad (i.e., site grading, pad construction, and shelter placement) times the total area of the fenced compound plus 10-foot perimeter area, and to construction of the access road. The emission factor is derived in Attachment A.
- The fugitive dust generated by trenching for the fiber optic cables and utility installation is simulated by a dirt/debris pushing emission factor published in the CEQA Air Quality Handbook of the South Coast Air Quality Management District. The emission factor is derived in Attachment A.
- Each piece of construction equipment is used at its full power emission factor to be conservative (i.e., load factor =1).